## In the Claims

This listing of claims replaces all prior versions and listings of claims:

- 1. (Previously Presented) A custom display and storage system comprising:
  - a display unit having an opening, said opening adapted for display of an image or character string;
  - a customizable insert assembly adapted for display of an image or character string, said insert assembly including a matting, said matting including a cut out corresponding to said opening of said display unit, said cut out being smaller than said opening;
  - a releasable connection between said display unit and said insert assembly adapted to removably mount said insert assembly to said display unit, and
  - a storage unit coupled with said display unit.
- 2. (Original) The custom display and storage system as claimed in claim 1 wherein said insert assembly further comprises a base sheet for mounting of the image or character string.
- 3. (Original) The custom display and storage system as claimed in claim 2 wherein said base sheet further comprises guidelines adapted for alignment of the image or character string.
- 4. (Original) The custom display and storage system as claimed in claim 1 wherein said releasable connection comprises a backing coupled with said display unit.
- 5. (Original) The custom display and storage system as claimed in claim 4 wherein said backing includes an elongate slot.

INVENTOR: SEYMOUR et al. Serial No. 10/764.977

6. (Original) The custom display and storage system as claimed in claim 4 wherein said backing is coupled to said display unit via a hinge.

- 7. (Previously Presented) The custom display and storage system as claimed in claim 1 wherein said storage unit comprise an album.
- 8. (Previously Presented) A custom display system comprising;
  - a frame, said frame including a lip;
  - a transparent display panel supported within a front side of said frame by said lip;
  - a single piece spacer positioned within said frame on an opposing side of said panel to said lip; and
  - a backing positioned on an opposing side of said spacer to said panel, said backing adapted to maintain said spacer and said panel within said frame from a back side of said frame; and
  - wherein said backing generally extends across the entire center of said frame to provide an enclosed space within said frame between said panel and said backing.
- 9. (Original) The custom display system as claimed in claim 8 wherein said backing comprises a matting component and a backing component.
- 10. (Original) The custom display system as claimed in claim 8 wherein said spacer has a width similar to a width of said lip.
- 11. (Original) The custom display system as claimed in claim 8 wherein said spacer has an inner circumference generally similar to an outer circumference of said lip.
- 12. (Withdrawn) A method of manufacturing a spacer for providing a gap between a display panel and a backing in a three dimensional custom display system, comprising the steps of:

10/764.977

determining an inner circumference of the display system;

determining outer circumferences of the display panel and the backing; and

injection molding a single piece body, said body including an outer circumference that fits within said inner circumference of the display system and an inner circumference that is less than the outer circumferences of both the display panel and the backing.

- 13. (Previously Presented) The custom display system as claimed in claim 8 wherein said backing includes an access panel to said enclosed space.
- 14. (Previously Presented) The custom display system as claimed in claim 8 wherein said spacer is positioned within said frame without the use of an adhesive.
- 15. (Previously Presented) The custom display system as claimed in claim 8 wherein said backing is located generally at a back-most edge of said back side of said frame.
- 16. (Previously Presented) The custom display system as claimed in claim 15 wherein said backing is flush with said back side of said frame.
- 17. (Previously Presented) The custom display system as claimed in claim 15 wherein said backing is mounted to said back side of said frame.